

## Pergo Langeland



Pergo parquet Svalbard, has following specifications:

- The parquet floor covering consists of panels of:
  - o 2400 x 260 x 14 mm.
- The floor covering must contain the following:
  - o Spruce coreboard of 9 mm thickness
  - o Toplayer is Oak and 3,2 mm thickness
  - o Finishing can be UV cured water based lacquer (7 layers) or UV cured oil (2 layers)
  - o Spruce or Pine backinglayer of 2 mm thickness
- The parquet floor covering is PEFC and Nordic Ecolabel (Nordic Swan) certified.
- EPD's are available on request.
- The slipperiness is minimum class USRV 50-52 according to CEN/TS 15676.
- The flooring panels have a formaldehyde emission class E1. The flooring is class A+ (very low VOC emission) for the indoor air quality. Parquet floor covering, with CE mark according to EN 14342:2008.
- The fire resistance class of the parquet floor covering, including the underlay prescribed by the manufacturer, is D<sub>fl</sub>-s1 according to EN 13501-1.
- The parquet floor covering must correspond minimum to a falling sand test with a score of 500-1700 according to SIS 923509.
- The parquet floor benefits a lifetime warranty for residential use. For commercial application upon request.
- Thermal resistance of the parquet floor is 0.14 m<sup>2</sup>K/W.
- Installation can be done:
  - o Floatingly
  - o Glued
  - o Connection on short side can be done in 3 ways:
    - Fold down
    - Snapping
    - Rotating
  - o Unlimited possibility to uplift and RE-install has to be allowed without any quality loss
- Expansion gaps will be covered by wallbases or profiles with matching decors.
- Décor can be chosen in the collection Langeland.