

Pergo laminate classic plank, public extreme has following specifications:



- The laminate floor covering consists of panels of 1200 x 190 x 9 mm and has no V-grooves.
- The laminate floor covering has permanent anti-static characteristics ($\leq 2\text{kV}$) according to EN 1815.
- Every panel has an invisible hydroseal coating at the tongue and groove to make the Pergo Public Extreme Classic Plank water resistant. In combination with the waterproof and flexible Pergo Aqua Sealant for sealing the perimeter expansion joints, you create a water resistant laminate floor.
- The slipperiness is minimum class DS according to EN 13893.
- The flooring panels have a formaldehyde emission class E1, with a maximal emission of 0.020ppm. The flooring is class A+ (very low VOC emission) for the indoor air quality. Laminate floor covering, according to EN 13329, with CE mark according to EN 14041.
- The fire resistance class of the laminate floor covering, including the underlay prescribed by the manufacturer, is B_{fl}-s1 according to EN ISO 9239-1.
- The laminate floor covering must correspond minimum to class 34 according to EN 13329. Class 34 is suitable for very high commercial use, as defined in EN 13329.
- The technical characteristics in respect to swelling, wear, impact, scratch and hard castor chair wheels (type H) resistance, staining, cigarette burns and light fastness, have at least to satisfy the requirements of EN 13329. Wear class of the floor is AC6 and the moisture swelling is $\leq 8\%$.
- The laminate flooring should have a build in technology which increases the resistance against micro scratching to a large extent. This characteristic enables to keep the new aspect for a longer period and to remain easy to maintain.
- The laminate floor covering is PEFC, Nordic Ecolabel (Green Swan) and EU-Ecolabel certified. EPD's are available on request.
- The panels have to be installed WITHOUT glue, by means of a mechanical connection which allows the panels to be angled or to be inserted horizontally lengthwise. The panels must allow uplift and reinstallation for a limited number of times without any quality loss.
- Expansion gaps will be covered by wallbases or INCIZO profiles with matching decors.
- Décor can be chosen in the collection Classic Plank, public extreme.