

# TECHNICAL DATA SHEET

## Pergo Langeland

Edition

10.2016



### General data

Panel	2400 x 260 mm		
Total thickness	14 mm		
Numbers of panels per pack	4		
m <sup>2</sup> per pack	2.496 m <sup>2</sup>		

### Panel build up

Toplayer	PEFC controlled sources	3.2 mm	
Core board	Spruce		
Backing layer	PEFC controlled sources	Spruce or Pine	2 mm
Tongue and groove	Length	Uniclic	
	Width	Perfect Fold 3.0 Connection	

### Surface layer

Wood species	Oak		
Origine	Europe		
Finishing	Extra Matt lacquer/ Natural extra matt UV-hardening oil / Black extra matt UV-hardening oil		

### Installation

Floating	On Pergo underlay	CF installation instructions
Glued to subfloor	Pergo MS polymere resin	CF installation instructions

### Warranty

Domestic use	Conditions in each pack	33 years
Uniclic connection	Lifetime	
Commercial	On request	

### Finishing

oiled			2 layers
UV curing varnish			5 - 7 layers
Wear resistance	SIS 923509	Falling sand	800 - 1000
	DIN 68861	S 33	100 - 1050
Scratch resistance	Anti-scratch top coat		
Stain resistance	EN 13442	All except blue ink	class 5
		Blue ink	class 3
CE	EN 14342: 2013	DOP PW 0502	
Castor chairs	Use soft castors, type W (EN 12529) and/or suitable office mat		
Slip resistance	CEN/TS 15676	USRV 50-52	
Emission of formaldehyde	EN 717-1	E1	
PCP	below detection limit		
Heat resistance	EN 12664	0.14 m <sup>2</sup> KW	
Underfloor heating	Suitable	CF special installation instructions	
Reaction to fire	EN 14342	CWFT	Dfl-s1

### Ecological certificates

U-zeichen	Z 156.606-898
AFFSET	A
Nordic ecolabel	3029-0001
PEFC	PEFC/07-32-37
M1	OK
EPD	On request

